



RIG# 17

SST ENERGY CORPORATION

OWI 1000-EH

SPECIFICATIONS

| | |
|-----------------------------|---|
| Drawworks | <i>OWI 1000EH with 1-1/4" line</i> |
| Drawworks horsepower | <i>1200 hp</i> |
| Hoisting Capacity | <i>630,000 lbs.</i> |
| Pumps | <i>2 X F-1600; 1600hp</i> |
| Pump pressure | <i>7500 psi</i> |
| Mobility | <i>Walking- up to 120'</i> |
| Engines | <i>3 X Cummins QSK-50 1,100 KW Tier II</i> |
| Controls | <i>Omron SCR/VFD</i> |
| Top Drive | <i>Canrig 275 ton</i> |
| Floor automation | <i>TM-80 and Auto Catwalk</i> |
| Mast | <i>DSII 750,000lbs on 12 lines</i> |
| Substructure | <i>Clear height 22' 8"; Floor Height 27'</i> |
| Rotary table | <i>27.5"</i> |
| Mud system | <i>1000 bbl.</i> |
| Shale shakers | <i>2 X Brandt King Cobra Venom</i> |
| Solids Control | <i>Two cone desander and 16 cone desilter</i> |
| BOP Equipment | <i>As Requested</i> |
| Accumulator | <i>5 station -10 (12 gallon) Bottles</i> |
| Choke Manifold | <i>10,000 psi</i> |
| Gas Buster | <i>Yes</i> |
| Boiler | <i>125 hp</i> |
| Fuel | <i>20,000 gallons</i> |
| Water | <i>500 bbl.</i> |
| | <i>Duel Fuel capable</i> |

***Modifications available as required**